

Thread Sealing Paste with Flax Fibres

Edition: 14 October 2026 | Version 1.1

Product and applications

NAZAR sealing paste based on the universal paste with finely chopped flax fibres added. The manufacturer declares 1% flax fibres by weight. Intended for metal threaded joints in heating, industrial and non-potable water installations. Helps assembly and later disassembly. The fibres are already included in the paste.

Technical data

Property	Manufacturer's specification
Appearance	Greasy grey paste with finely chopped flax fibres
Odour	Rapeseed oil odour
Flax fibre content	1% by weight, as declared by the manufacturer
Operating temperature range	-30°C to +140°C
Maximum operating pressure	25 bar

Operating parameters are manufacturer specifications.

Application

Clean the threads. Apply the paste containing flax fibres to the thread and tighten the joint following the instructions of the pipe and fitting manufacturers.

Storage and shelf life

Store in tightly closed containers in a dry, well-ventilated area, away from food, drinks and incompatible materials. The manufacturer declares an indefinite shelf life when stored correctly.

Product documentation and precautions

Not intended for drinking-water installations. Gas documentation for this version is being prepared. The certificate for the universal paste does not cover this product. Refer to the current Safety Data Sheet for this product. Keep out of reach of children and avoid contact with eyes. Follow the product Safety Data Sheet.

Packaging

Net contents	Packaging	Product code	EAN
75 g	Tube	NAZ-L-75	5907678808271
150 g	Can	NAZ-L-150	5907678808257
300 g	Can	NAZ-L-300	5907678808264

Manufacturer

PPU "NAZAR" Andrzej Nazarowicz
ul. Witosa 22, 11-600 Węgorzewo, Poland
Tax identification number (NIP): 845-103-59-44
Tel./fax: +48 87 427 18 38; mobile: +48 502 098 077
E-mail: nazar@nazar.pl; website: www.nazar.pl