

Universal Thread Sealing Paste

Edition: 14 October 2026 | Version 1.1

Product and applications

Non-hardening paste for sealing metal threaded joints together with sealing flax. Designed for indoor and outdoor water, gas and heating installations. Helps protect threads from corrosion and makes later disassembly easier.

Technical data

Property	Manufacturer's specification
Appearance	Grey paste
Odour	Rapeseed oil odour
Operating temperature range	-30°C to +140°C
Maximum operating pressure	20 bar

Operating parameters are manufacturer specifications.

Application

Use together with sealing flax. Apply to the threaded joint during assembly, following the instructions for the pipes and fittings. In drinking-water installations, remove excess product from surfaces in contact with water and rinse thoroughly after assembly.

Storage and shelf life

Store in tightly closed containers in a dry, well-ventilated area, away from food, drinks and incompatible materials. The manufacturer declares an indefinite shelf life when stored correctly.

Product documentation and precautions

Hygienic certificate B.BK.60110.1388.2024 covers drinking-water use subject to its stated conditions. It ceases to be valid after 23 December 2027 or if the formulation or manufacturing technology changes. Keep out of reach of children and avoid contact with eyes. Follow the product Safety Data Sheet.

Packaging

Net contents	Packaging	Product code	EAN
150 g	Can	NAZ-U-150	5907678808097
300 g	Can	NAZ-U-300	5907678808080
500 g	Can	NAZ-U-500	5907678808073

Manufacturer

PPU "NAZAR" Andrzej Nazarowicz
ul. Witosa 22, 11-600 Węgorzewo, Poland
Tax identification number (NIP): 845-103-59-44
Tel./fax: +48 87 427 18 38; mobile: +48 502 098 077
E-mail: nazar@nazar.pl; website: www.nazar.pl